

MOD 3~10KTL3-XH

- Battery ready, future proof
- Dual MPP Trackers
- Type II SPD on DC and AC side
- AFCI function optional
- 24h self-consumption monitoring



GROWATT

www.ginverter.com

P O W E R
- I N G
T O M O R R O W

Primary

Datasheet	MOD 3000TL3-XH	MOD 4000TL3-XH	MOD 5000TL3-XH	MOD 6000TL3-XH	MOD 7000TL3-XH	MOD 8000TL3-XH	MOD 9000TL3-XH	MOD 10KTL3-XH
Input data (DC)								
Max. recommended PV power (for module STC)	6000W	8000W	10000W	12000W	14000W	16000W	18000W	20000W
Max. DC voltage	1100V							
Start voltage	160V							
Nominal voltage	600V							
MPPT voltage range	140V-1000V							
No. of MPP trackers	2							
No. of PV strings per MPP tracker	1							
Max. input current per MPP tracker	16A							
Max. short-circuit current per MPP tracker	20A							
Input data (DC battery)								
Compatible battery	ARK XH Battery System(7.68kWh-25.6kWh)							
Operating voltage range	600 V-950 V							
Max.operating current	11A				18.5A			
Max.charge power	6000W				10000W			
Max.discharge power	3300W	4400W	5500W	6600W	7700W	8800W	9900W	11000W*
Output data (AC)								
AC nominal power	3000W	4000W	5000W	6000W	7000W	8000W	9000W	10000W
Max. AC apparent power	3300VA	4400VA	5500VA	6600VA	7700VA	8800VA	9900VA	11000VA*
Nominal AC voltage (range*)	220V/380V, 230V/400V (340-440V)							
AC grid frequency (range*)	50/60 Hz (45-55Hz/55-65 Hz)							
Max. output current	5.0A	6.7A	8.3A	10.0A	11.7A	13.3A	15.0A	16.7A
Adjustable power factor	0.8leading...0.8lagging							
THDi	<3%							
AC grid connection type	3W+N+PE							
Efficiency								
MAX. efficiency	98.3%	98.3%	98.3%	98.3%	98.6%	98.6%	98.6%	98.6%
European efficiency	97.5%	97.5%	97.5%	97.5%	98.1%	98.1%	98.1%	98.1%
MPPT efficiency	99.9%							
Protection devices								
DC reverse polarity protection	Yes							
DC Switch	Yes							
AC/DC surge protection	Type II / Type II							
Insulation resistance monitoring	Yes							
AC short-circuit protection	Yes							
Ground fault monitoring	Yes							
Grid monitoring	Yes							
Anti-islanding protection	Yes							
Residual-current monitoring unit	Yes							
String fault monitoring	Yes							
AFCI protection	Optional							
General data								
Dimensions (W / H / D)	425/387/147mm	425/387/147mm	425/387/147mm	425/387/147mm	425/387/178mm	425/387/178mm	425/387/178mm	425/387/178mm
Weight	12.5kg	12.5kg	12.5kg	12.5kg	14kg	14kg	14kg	14kg
Operating temperature range	- 25°C ... +60°C							
Nighttime power consumption	< 5.5W							
Topology	Transformerless							
Cooling	Natural convection							
Protection degree	IP66							
Relative humidity	0~100%							
Altitude	4000m							
DC connection	H4/MC4(Optional)							
AC connection	Connector							
Display	OLED+LED/WIFI+APP							
Interfaces: USB/RS485/WIFI /GPRS/LAN/RF	Yes/Yes/Optional/Optional/Optional/Optional							
Warranty: 5 years /10 years	Yes/Optional							
CE, VDE0126, Greece, EN50549, C10/C11, VFR 2019, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, N4105, TOR Erzeuger G98/G99, G100, AS4777, UNE217001, UNE206007, PO12.2								

* For Belgium C10/C11, MOD 10KTL3-XH max. battery discharge power is limit to10000W and max. output power is limit to 10000VA.

* The AC voltage range and frequency range may vary depending on specific country grid standard.
All specifications are subject to change without notice.